

BOSS™ SEATS



Installation Instructions

1. Remove the stock seat.

Pull up on the latch at the front of the seat, and slide the seat backwards.

2. Clean the gas tank.

Thoroughly clean the gas tank with acetone or a similar solvent. Lacquer thinner works well for this.

3. Fasten the Velcro.

When the tank is clean and dry, line up the BOSS seat, and mark on the gas tank where the seat will mount correctly. Fasten the included strips of hook Velcro on the gas tank so they will match up with the loop Velcro on the bottom of the seat when you put it on. Hook the loop on the rear of the seat around the back of the tank, and pull the seat forward; making sure that the seat lies in the stock position.

4. Fasten the snaps.

Now that the seat is attached to the tank, pull the snap flaps forward and down. (Pull forward to remove any wrinkles from the side panel, and then pull down to match the tunnel line.) Mark the tunnel where you would like to mount the snap studs. An easy trick to help you mark for the snaps accurately is to apply a strip of masking tape along the tunnel in the general area where the snaps will go. Then, as you pull the flaps forward and down, press the snap on the flap against the masking tape. This will leave an imprint on the tape of the exact location for drilling the holes. Drill the holes and remove the masking tape from the tunnel. Attach the snap studs using the supplied rivets, and then attach the flaps to the installed studs.

5. Clean up & ride.

Now that the seat is installed, blow it off with air or wipe with a damp cloth.

NOTE: Material has been treated with UV inhibitors, however all vinyls and fabrics last longer if kept out of the sun for long periods of time.